

HUSKY CENTRAL VACUUM POWER UNITS: NEW PRODUCT SPECIFICATIONS. 2008

FEATURES / MODEL:	Q COMPACT	Q AIR	Q AIR CYKLON	Q WHISPER	Q PRO 3611	Q PRO 3211	H²O
Waterlift (mm WS)	2802	2955	2955	3759	3411	4470	3683
Airflow (Litres/s)	56.0	52.4	52.5	62.9	48.0	50.7	92.5
Air Watts	463	594	594	653	548	757	1050
Vacuum Pressure	27.44	28.95	28.95	36.83	33.42	43.85	36.08
Amps	5.0	8.0	8.0	8.0	7.6	6.9 & 6.3	2 x 7.8
Volts	240	240	240	240	240	240	240
Max. Input Watts	1144	1853	1853	1828	1748	1510 & 1501	2 x 1760
Soft Start Control System	no	yes	yes	no	yes	yes	yes
Ventable	yes/adjustable outlet	yes	yes	yes	yes	yes	yes
Utility Inlet Included	no	yes	yes	yes	no	no	no
Debris Capacity (Litres) & Type	8 antibacterial bag	15 antibacterial bag	16 bucket	22 bucket	26 bucket	26 bucket	22 bucket
Longest Pipe Run	40m	90m	90m	100m	100m	140m	100m
Coverage (sq. m/ft)	200/2000	600/6000	600/6000	800/8000	500/5000	1200/12000	800/8000
Est. Max. Inlets	6	12	15	20	25	30	25
Size	56cm h x 33cm Ø	72cm h x 33cm Ø	87cm h x 33cm Ø	84cm h x 33cm Ø	76cm h x 40cm Ø	76cm h x 40cm Ø	98cm h x 35cm Ø
Wet Pick-Up	no	no	no	no	yes	yes	yes
Filter Type	antibacterial filter bag	antibacterial filter bag	polypropylene/corlon self cleaning	polypropylene/corlon washable	polyester washable	polyester washable	polyester washable
Motor size (no. of stages)	5.7"/145mm/1	5.7"/145mm/2	5.7"/145mm/2	5.7"/145mm/2	5.7"/145mm/3	2 x 5.7"/145mm/4	2 x 7.2"/183mm/6
Est. Carbon Brush Life (hrs)	500	750	750	650	750	750	1200
Intelligent Performance Monitor Light (IPM)	no	yes	yes	yes	yes	yes	yes
Motor Protection System	yes	yes	yes	yes	yes	yes	yes
Sound Level (dbA)	70	70	72	60	71	72	72
Lid Colour & Material	spun aluminum	spun aluminum	spun aluminum	spun aluminum	spun aluminum	spun aluminum	black ABS starex
Upper Cylinder Colour	black metal	stainless steel	stainless steel	black metal	stainless steel	stainless steel	black ABS starex
Dirt Bucket Colour & Material	n/a	n/a	spun aluminum	spun aluminum	polyethylene	polyethylene	black ABS starex